



**ZENITH** INDUSTRIAL RUBBER  
PRODUCTS PVT. LTD.  
*Quality Rubber Solutions*

An ISO 9001:2008 Registered Company  
An ISO 14001:2004 Registered Company

## GOVT.RECOGNISED EXPORT HOUSE

## TECHNICAL SPECIFICATIONS

QUALITY : 100% EPDM CODE: EP 65125

PROPERTIES	TEST METHOD	VALUES	TEST METHOD	VALUE
		FPS UNITS		METRIC UNITS
SPECIFIC GRAVITY	DIN 53508	1.25	ASTM D297	1.25
HARDNESS	DIN 53505	65 ± 5 Sh A	ASTM D2240	65 ± 5 Sh A
TENSILE STRENGTH ( min )	DIN 53504	1140 PSI	ASTM D412	80 kg/cm2
ELONGATION AT BREAK ( min ) %	DIN 53504	350	ASTM D412	350
COMPRESSION SET (70°C/24 hrs/25% set) (max) %	DIN 53517	40	ASTM D395 METHOD B	40
TEAR RESISTANCE ( Angular ) min	DIN 53515	123.2 Lbs/Inch	ASTM D624	22 Kg/cm
CHANGE IN PROPERTIES				
HEAT AGEING ( 72 hrs. AT 70°C )			ASTM D573	
--- HARDNESS (Pts)		+ 3 (Max)		+ 3 (Max)
--- TENSILE STRENGTH (%)		+ 10 / - 10		+ 10 / - 10
--- ELONGATION AT BREAK (%)		+ 10 / - 20		+ 10 / - 20
VOLUME SWELL : AT 70° C FOR 72 HRS/IN			ASTM D 471	
IRM OIL NO.1		Not Recommended		Not Recommended
IRM OIL NO.2		Not Recommended		Not Recommended
IRM OIL NO.3		Not Recommended		Not Recommended
POLYMER CONTENT (EPDM)		100%		100
CHEMICAL RESISTANCE				
---				
OZONE@100PPHM/72HRS/40°C/20%STRETCH		EXCELLENT	ASTM D 1149	EXCELLENT
--- DILUTE ACIDS AND BASES		EXCELLENT		EXCELLENT
--- CONCENTRATED ACIDS AND BASES		EXCELLENT		EXCELLENT
TEMPERATURE RANGE		-40° to + 130° C		-40° to + 130° C
COLOUR		BLACK		BLACK



A/2, PAREKH MAHAL, 80 VEER NARIMAN ROAD, CHURCHGATE MUMBAI - 400 020.

Email: [info@zenithrubber.com](mailto:info@zenithrubber.com)

Website: [www.zenithrubber.com](http://www.zenithrubber.com)